

VENT-SEAL

SPRAY FOAM

VENT-SEAL IS:

Self-contained two component spray foam pack.

A pack consists of two light weight cylinders containing an isocyanurate catalyst and polyol resin ,dispensing gun and kit containing four spare nozzles, safety gloves and goggles and the instructions. The foam is rigid and has a soft pink colour.



TECHNICAL DATA:

- Pack weight approx. 17 kg
- Pack yield approx. 0.33 cubic metres
- Foam density approx. 30 kg per cubic metre
- Thermal conductivity approx. 0.03 W/m degC
- 25 mm layer provides an air tight seal
- SA Government mining Engineer approval
GME14/26/3
- CSIR Test Reports: BF200/13 5600 5664
BF202/104 5600 5664
BF203/003 5600 5664 & Bf204/004 5600 5664
- Risk Assessments: South African & Australian

APPLICATIONS:

- Creating air tight barriers
- Sealing porous surfaces
- Creating thermal barriers
- Sealing / Filling cavities

Aerocell (Pty) Ltd

Made in South Africa



VENT-SEAL

SPRAY FOAM



AEROCELL (PTY) LTD

4 Boniface Road
Selection Park Industrial Sites
Springs, 1560
South Africa

PO Box 2203
Springs
1560
South Africa

Telephone: +27 11 815 5045

Fax: +27 11 815 6061