



Ex 'nR' & WP Well Glass Lighting Fixture Suitable For Zone- 2

● Technical Data : 40031

ENCLOSURE :

Ex 'nR' RESTRICTED BREATHING AS PER IS/IEC 60079-15:2005

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -2

CERTIFICATION :

CIMFR/TC/P/H516

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST AL. ALLOY

RATING & TEMPERATURE CLASSIFICATION :

125W HPMV - T4
200W GLS - T4
160W MLL - T3
70W HPSV - T5
150W METAL HALIDE - T4
2 x 32W CFL LAMP - T6

TRANSPARENT PART :

BOROSILICATED HEAT RESISTANT, CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN ENCLOSED BREAK WITH BUILT-IN TERMINAL, ES-27

INTERNAL REFLECTOR :

MIRROR POLISHED

WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) EXTERNAL REFLECTOR
- 4) PAINT SHADE AS PER CLIENT REQUIREMENT
- 5) LAMP
- 6) STAINLESS STEEL WIRE GUARD

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) MIRROR POLISHED INTERNAL REFLECTOR

