



SINCE 1974

Ex 'nR' LED Bay Fixture For Zone - 2

● Technical Data : 40031

ENCLOSURE :

Ex 'nR' RESTRICTED BREATHING AS PER IS/IEC 60079-15:2005

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -2

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST AL. ALLOY

RATING & TEMPERATURE CLASSIFICATION :

45W LED, 250V, AC 50/60Hz & T6

TRANSPARENT PART :

SPECIALLY DESIGNED BOROSILICATE ANGULAR LENS FOR WIDER LIGHT DISTRIBUTION

COMPONENTS :

- 1) LED MODULE 45W
- 2) SUITABLE DRIVER
- 3) VIBRATION PROOF 2 WAY TERMINAL BLOCK

FINISH :

SIEMENS GREY

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) PAINT SHADE AS PER CLIENT REQUIREMENT
- 4) EXTERNAL REFLECTOR

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) PRESSURE DIE CAST ENCLOSURE
- D) REPLACES 125W HPMV, 80W HPMV, & 70W MH, LAMP
- E) ENERGY EFFICIENT AS IT CONSUMES ONLY 45W
- F) STD. COLOUR TEMPERATURE 6500K

