

Industrial Weatherproof LED Well Glass Fixture

● **Technical Data : 40031**

ENCLOSURE :

WEATHERPROOF SUITABLE FOR INSTALLATION IN SAFE AREA

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST AL. ALLOY

RATING :

60W LED, 250V, AC 50/60Hz

TRANSPARENT PART :

DIFFUSED POLY CARBONATE DOME

COMPONENTS :

- 1) LED MODULE 60W
- 2) SUITABLE DRIVER
- 3) 2 WAY TERMINAL BLOCK

FINISH :

SIEMENS GREY

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) PAINT SHADE AS PER CLIENT REQUIREMENT

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) PRESSURE DIE CAST ENCLOSURE
- D) REPLACES 150W MH, 250W HPMV LAMP
- E) ENERGY EFFICIENT AS IT CONSUMES ONLY 60W
- F) STD. COLOUR TEMPERATURE 6500K

