

Industrial Weatherproof FloodLight LED Fixture

● Technical Data : 40031

ENCLOSURE :
WEATHERPROOF SUITABLE FOR INSTALLATION
IN SAFE AREA

PROTECTION :
IP-66 AS PER IS/IEC 60529:2001

MATERIAL OF CONSTRUCTION :
PRESSURE DIE CAST AL. ALLOY

RATING :
45W LED, 250V, AC 50/60Hz

TRANSPARENT PART :
SPECIALLY DESIGNED BOROSILICATE ANGULAR
LENS FOR WIDER LIGHT DISTRIBUTION

COMPONENTS :
1) LED MODULE 45W
2) SUITABLE DRIVER
3) 2 WAY TERMINAL BLOCK

FINISH :
SIEMENS GREY

HARDWARE :
STAINLESS STEEL

EARTHING :
1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :
M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :
1) MOUNTING BRACKET
2) CABLE GLAND & STOPPING PLUG
3) PAINT SHADE AS PER CLIENT REQUIREMENT

SPECIAL FEATURES :
A) SUPERIOR POWDER COATED EPOXY FINISH
B) NON FALLING TYPE EXTERNAL HARDWARE
C) PRESSURE DIE CAST ENCLOSURE
D) REPLACES 125W HPMV, 80W HPMV &
70W MH LAMP
E) ENERGY EFFICIENT AS IT CONSUMES ONLY 45W
F) STD. COLOUR TEMPERATURE 6500K

