

Industrial Weatherproof FloodLight LED Fixture

● **Technical Data : 40031**

ENCLOSURE :
WEATHERPROOF SUITABLE FOR INSTALLATION
IN SAFE AREA

PROTECTION :
IP-66 AS PER IS/IEC 60529:2001

MATERIAL OF CONSTRUCTION :
PRESSURE DIE CAST AL. ALLOY

RATING :
60W LED, 250V, AC 50/60Hz

TRANSPARENT PART :
SPECIALLY DESIGNED BOROSILICATE ANGULAR
LENS FOR WIDER LIGHT DISTRIBUTION

COMPONENTS :
1) LED MODULE 60W
2) SUITABLE DRIVER
3) 2 WAY TERMINAL BLOCK

FINISH :
SIEMENS GREY

HARDWARE :
STAINLESS STEEL

EARTHING :
1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :
M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :
1) MOUNTING BRACKET
2) CABLE GLAND & STOPPING PLUG
3) PAINT SHADE AS PER CLIENT REQUIREMENT

SPECIAL FEATURES :
A) SUPERIOR POWDER COATED EPOXY FINISH
B) NON FALLING TYPE EXTERNAL HARDWARE
C) PRESSURE DIE CAST ENCLOSURE
D) REPLACES 150W MH, 250W HPMV LAMP
E) ENERGY EFFICIENT AS IT CONSUMES ONLY 60W
F) STD. COLOUR TEMPERATURE 6500K

