



Flameproof & Weatherproof Reaction Vessel Lamp

● Technical Data : FCG/RV/103-1

ENCLOSURE :

Ex-d, GAS Gr. IIA & IIB AS PER IS/IEC 60079-1:2007 & IS/IEC 60079-0:2004

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE - 1 & 2

CERTIFICATION :

ERTL(E)/TES/F044/0090/09-08

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINIUM ALLOY.

RATING & TEMPERATURE CLASSIFICATION :

60 Watt GLS LAMP - T6

18/20 Watt CFL LAMP - T6

100 Watt GLS LAMP - T5

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR FLAT GLASS

LAMP HOLDER :

PORCELAIN E-27

SWITCH :

16A, DP, ON-OFF, 250V, A.C. 50Hz

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) CABLE GLAND & STOPPING PLUG
- 2) PAINT SHADE AS PER CLIENT REQUIREMENT.
- 3) LAMP
- 4) 7W LED LAMP
- 5) WITH TIMER & PUSH BUTTON

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) EASY TO REPLACE THE LAMP

NOTE:

THIS LIGHT FIXTURE IS ALSO AVAILABLE FOR GAS Gr. IIC.

