



Ex 'nR' & Weatherproof Well Glass Lighting Fixture

● Technical Data : FCG/W/403-3

ENCLOSURE :

Ex 'nR' RESTRICTED BREATHING AS PER IS/IEC 60079-15:2005

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -2

CERTIFICATION :

CIMFR/TC/P/H413

MATERIAL OF CONSTRUCTION :

CAST ALUMINIUM ALLOY.

RATING & TEMPERATURE CLASSIFICATION :

400 Watt HPMV - T3

400 Watt HPSV - T4

500 Watt GLS - T3

250 Watt MLL - T4

400 Watt MH - T4

TRANSPARENT PART :

BOROSILICATED HEAT RESISTANT, CLEAR DOME GLASS

LAMP HOLDER :

ENCLOSED BREAK PORCELAIN ES-40

WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED.

INTERNAL REFLECTOR :

MIRROR POLISHED

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632 AS PER IS:5.

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

1) MOUNTING BRACKET

2) CABLE GLAND

3) EXTERNAL REFLECTOR

4) PAINT SHADE AS PER CLIENT REQUIREMENT.

5) LAMP

SPECIAL FEATURES :

A) SUPERIOR POWDER COATED EPOXY FINISH

B) NON FALLING TYPE EXTERNAL HARDWARE

C) MIRROR POLISHED INTERNAL REFLECTOR

