



Flameproof & Weatherproof Bulkhead Fixture

● Technical Data : LB 31223 / LB 61223

ENCLOSURE :

Ex-d, GAS Gr. IIA IIB & IIC AS PER IS/IEC 60079-1:2007

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE 1 & 2

CERTIFICATION :

ERTL(E)/TES/F042/0081/07-04

MATERIAL OF CONSTRUCTION :

CAST ALUMINIUM ALLOY

RATING & TEMP. CLASSIFICATION :

2 x 23 Watt CFL - T6 (SELF BALLAST)

2 x 26 Watt CFL - T6

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR FLAT GLASS

INTERNAL REFLECTOR :

AL. ANODIZED (DEEP DRAWN)

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED
632 AS PER IS:5.

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL AT EXTRA COST :

1) PAINT SHADE AS PER CLIENT
REQUIREMENT

2) S.S. FRAME FOR FRONT SIDE

NOTE :

LAMP REPLACEMENT ARRANGEMENT
IS FROM THE FRONT SIDE.



BOTTOM OPENABLE

