



Flameproof & Weatherproof Integral Bulkhead Fixture

● **Technical Data : LB 61125**

ENCLOSURE :

Ex-d, GAS Gr. IIC AS PER IS/IEC 60079-1:2007

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -1 & 2

CERTIFICATION :

CMRI/TC/P/H435

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINIUM ALLOY.

RATING & TEMPERATURE CLASSIFICATION :

125W HPMV & T4

COMPONENTS :

GEAR PLATE WITH FOLLOWING COMPONENTS

- A) BALLAST
- B) CAPACITOR & (IGNITOR FOR HPSV/MH LAMP)
- C) 2 WAY TERMINAL BLOCK

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR FLAT GLASS

LAMP HOLDER :

PORCELAIN E-27

WIRE GUARD :

M.S. GALVANIZED & WHITE EPOXY PAINTED

INTERNAL REFLECTOR :

ALUMINIUM ANODISED

FINISH :

DARK GREY EPOXY SHADE 632
AS PER IS:5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL AT EXTRA COST :

- 1) CABLE GLAND & STOPPER
- 2) S.S. FRAME FOR FRONT SIDE



BOTTOM OPENABLE

