

Industrial Weatherproof LED Bay Fixture

Technical Data: 40031

ENCLOSURE:

WEATHERPROOF SUITABLE FOR INSTALLATION IN SAFE AREA

PROTECTION:

IP-66 AS PER IS/IEC 60529:2001

MATERIAL OF CONSTRUCTION:

PRESSURE DIE CAST AL. ALLOY

RATING :

90W LED, 250V, AC 50/60Hz

TRANSPARENT PART:

SPECIALLY DESIGNED BOROSILICATE ANGULAR LENS FOR WIDER LIGHT DISTRIBUTION

COMPONENTS:

- 1) LED MODULE 90W
- 2) SUITABLE DRIVER
- 3) 2 WAY TERMINAL BLOCK

FINISH:

SIEMENS GREY

HARDWARE:

STAINLESS STEEL

EARTHING

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY:

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST:

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) PAINT SHADE AS PER CLIENT REQUIREMENT

SPECIAL FEATURES:

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) PRESSURE DIE CAST ENCLOSURE
- D) REPLACES 400W HPMV, 250W MH, LAMP
- E) ENERGY EFFICIENT AS IT CONSUMES ONLY 90W
- F) STD. COLOUR TEMPERATURE 6500K



