



# Flameproof & Weatherproof Hand Lamp Fitting

## ● Technical Data : LH 31060

### ENCLOSURE :

Ex-d, GAS Gr. IIA & IIB AS PER IS/IEC 60079-1:2007  
& IS/IEC 60079-0:2004

### PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

### AREA CLASSIFICATION :

ZONE - 1 & 2

### CERTIFICATION :

ERTL(E)/TES/F042/0018/02-05

### MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINIUM ALLOY

### RATING & TEMPRATURE CLASSIFICATION :

60 Watt GLS LAMP - T6

100 Watt GLS LAMP - T6

### TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR DOME GLASS

### LAMP HOLDER :

PORCELAIN E-27

### WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED

### HARDWARE :

STAINLESS STEEL

### EARTHING :

1 No. INSIDE & 1 No. OUTSIDE

### FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

### CABLE ENTRY :

M20 x 1 No.

### OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) CABLE GLAND
- 2) PAINT SHADE AS PER CLIENT REQUIREMENT
- 3) LAMP

### SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) EASY TO REPLACE THE LAMP

### NOTE:

THIS LIGHT FITTING IS ALSO AVAILABLE FOR GAS Gr. IIC.

