



Ex 'nR' & WP Well Glass Fixture With Integrated Control Gear

● Technical Data : LW 21202

ENCLOSURE :

Ex 'nR' RESTRICTED BREATHING AS PER IS/IEC 60079-15:2005

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -2

CERTIFICATION :

CIMFR/TC/P/H933

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINIUM ALLOY

RATING & TEMPERATURE CLASSIFICATION :

80 Watt HPMV - T4

125 Watt HPMV - T4

70 Watt MH - T5

70 Watt HPSV - T5

42 Watt C.F.L - T6

COMPONENTS :

GEAR PLATE WITH FOLLOWING COMPONENTS

A) BALLAST

B) CAPACITOR

C) VIBRATIONPROOF 2 WAY TERMINAL BLOCK

D) IGNITOR FOR HPSV/MH LAMP

TRANSPARENT PART :

BOROSILICATED HEAT RESISTANT, CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN ENCLOSED BREAK WITH BUILT-IN TERMINAL, ES-27

INTERNAL REFLECTOR :

MIRROR POLISHED

WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED.

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

1) MOUNTING BRACKET

2) CABLE GLAND & STOPPING PLUG

3) EXTERNAL REFLECTOR

4) PAINT SHADE AS PER CLIENT REQUIREMENT

5) LAMP

6) STAINLESS STEEL WIRE GUARD

SPECIAL FEATURES :

A) SUPERIOR POWDER COATED EPOXY FINISH

B) NON FALLING TYPE EXTERNAL HARDWARE

C) MIRROR POLISHED INTERNAL REFLECTOR

