



SINCE 1974

Flameproof & Weatherproof Well Glass Lighting Fixture

● Technical Data : LW 31200

ENCLOSURE :

Ex-d, GAS Gr. IIA & IIB AS PER IS/IEC 60079-1:2007 & IS/IEC 60079-0:2004

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE - 1 & 2

CERTIFICATION :

ERTL(E)/TES/FO44/0088/09-08

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST ALUMINIUM ALLOY

RATING & TEMPERATURE CLASSIFICATION :

80/125W HPMV	- T4	2x26W C.F.L.	- T6
200W GLS	- T4	160W MLL	- T4
2x23W C.F.L.	- T6	100W GLS	- T6
70W HPSV	- T5	70/150W MH	- T4

(LED LAMP CAN BE OFFERED ON REQUEST)

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN E-27 / Bi-PIN TYPE FOR 26W CFL

INTERNAL REFLECTOR :

MIRROR POLISHED

WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED.

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) EXTERNAL REFLECTOR
- 4) PAINT SHADE AS PER CLIENT REQUIREMENT
- 5) LAMP
- 6) STAINLESS STEEL WIRE GUARD
- 7) CONTROL GEAR BOX FOR MV/MH/SV LAMP

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) MIRROR POLISHED INTERNAL REFLECTOR
- D) PRESSURE DIE CAST ENCLOSURE

