



SINCE 1974

Flameproof & Weatherproof Well Glass Lighting Fixture

● Technical Data : LW 31400

ENCLOSURE :

Ex-d, GAS Gr. IIA & IIB AS PER IS/IEC 60079-1:2007 & IS/IEC 60079-0:2004

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE - 1 & 2

CERTIFICATION :

ERTL(E)/TES/FO42/0046/08-05

MATERIAL OF CONSTRUCTION :

CAST ALUMINIUM ALLOY.

RATING & TEMPERATURE CLASSIFICATION :

400 Watt HPMV LAMP - T3

500 Watt GLS LAMP - T3

250 Watt MLL LAMP - T4

250 Watt MH LAMP - T4

250 Watt HPSV LAMP - T4

TRANSPARENT PART :

HEAT, RESISTANT & TOUGHENED CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN E-40

INTERNAL REFLECTOR :

MIRROR POLISHED

WIRE GUARD :

M.S. GALVANIZED & WHITE EPOXY PAINTED.

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) MOUNTING BRACKET
- 2) CABLE GLAND & STOPPING PLUG
- 3) EXTERNAL REFLECTOR
- 4) PAINT SHADE AS PER CLIENT REQUIREMENT.
- 5) LAMP
- 6) STAINLESS STEEL WIRE GUARD

SPECIAL FEATURES :

- A) SUPERIOR POWDER COATED EPOXY FINISH
- B) NON FALLING TYPE EXTERNAL HARDWARE
- C) MIRROR POLISHED INTERNAL REFLECTOR

NOTE:

THIS LIGHT FIXTURE IS ALSO AVAILABLE FOR GAS Gr. IIC.

