



Flp & Wp Twin Aviation Obstruction Light

● Technical Data : LW 51200

ENCLOSURE :

Ex-d, GAS Gr. IIA & IIB AS PER IS/IEC 60079-1:2007 & IS/IEC 60079-0:2004

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE 1 & 2

CERTIFICATION :

ERTL(E)/TES/F042/0023/02-05

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINIUM ALLOY

RATING & TEMPRATURE CLASSIFICATION :

7W LED LAMP, 230V AC - T6

TRANSPARENT PART :

HEAT, RESISTANT & TOUGHENED CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN E27

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

LAMP :

RED MEDIUM INTENSITY LED LAMP WITH E27 THREADED CAP, 7W, 230V AC

NOTE:

THIS LIGHT FIXTURE IS ALSO AVAILABLE FOR GAS Gr. IIC.



SINGLE



COMPACT



TWIN

