



Flameproof & Weatherproof Hooter/speaker

● Technical Data : MCH 3001 / MCH 6001

ENCLOSURE :

Ex-d, GAS Gr. IIA/IIb & IICAS PER IS/IEC 60079-1:2007

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE-1 & 2

CERTIFICATION :

ERTL(E)/TES/FO42/0020/02-05

MATERIAL OF CONSTRUCTION :

CAST ALUMINIUM ALLOY

RATING :

IN PUT VOLTAGE : Max. UPTO 230 Volts AC.

OR UPTO 110V. DC.

IN PUT POWER :

UPTO 25 W RMS

AND Max. 38 W.

IMPEDANCE/POWER :

400Ω/25 W

TAP ON 100V LINE :

500Ω/20 W

670Ω/15 W

1KΩ/10 W

2KΩ/05 W

FREQUENCY RESPONSE :

250 - 10 khz

SPL AT 1 khz :

122 db / 25W / 1m

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER

COATED 632 AS PER IS:5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

NAME PLATE :

STAINLESS STEEL

