



FLP/WP Flush Mounting Start-stop Push Button

● **Technical Data : PB 31202 / PB 61202**

ENCLOSURE :

Ex-d, GAS Gr. IIA / IIB & IIC AS PER IS/IEC 60079-1:2007

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -1 & 2

CERTIFICATION :

ERTL(E)/TES/FO42/0014/02-05

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST ALUMINIUM ALLOY

RATING & SURFACE TEMP. CLASS :

10A, 550V, AC, 50/60 Hz & T6

COMPONENTS :

- A) CONTACT ELEMENT 10A, 500V AC
- B) STOP PUSH BUTTON RED SHROUDED WITH "1NC" CONTACT - 01 No
- C) START PUSH BUTTON GREEN SHROUDED WITH "1NO" CONTACT - 01 No
- D) 4 WAY TERMINAL BLOCK - 1 No.

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED 632 AS PER IS:5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) CABLE GLAND & STOPPER
- 2) PAINT SHADE AS PER CLIENT REQUIREMENT



CUT OUT SIZE
405 x 185 ±3mm

