



FLP/WP Flush Mounting Rotary/Selector Switch

● Technical Data : PB 31207 / PB61207

ENCLOSURE :

Ex-d, GAS Gr. IIA / IIB & IIC AS PER IS/IEC 60079-1:2007

PROTECTION :

IP-65 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE -1 & 2

CERTIFICATION :

ERTL(E)/TES/FO42/0014/02-05

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST ALUMINIUM ALLOY

RATING & SURFACE TEMP. CLASS :

UPTO 32A, 550V, AC, 50/60 Hz & T6

COMPONENTS :

A) ON-OFF SWITCH, UPTO 32A, 415V AC - 1 No.

B) 4 WAY TERMINAL BLOCK - 1 No.

FINISH :

DAK ADMIRALTY GREY EPOXY POWDER COATED 632 AS PER IS-5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

1) CABLE GLAND & STOPPER

2) PAINT SHADE AS PER CLIENT REQUIREMENT



CUT OUT SIZE
405 x 185 ±3mm

